



NOTE:
IF IBC CERTIFICATION IS APPLICABLE
OR REQUIRED SEE SEISMIC ADV FOR
INSTALLATION INSTRUCTIONS.

DIMENSIONS IN [] ARE ENGLISH
STANDARD EQUIVALENTS

40 MODEL 4P5/4Q5/4Q7
 45 MODEL 4P7/4P8/4Q10
 50 MODEL 4P7/4Q10
 60 MODEL 4P8/4P7/4Q10
 60 MODEL 4V9
 RECONNECTABLE,
 IMPROVED MOTOR STARTING (IMS) RECONNECTABLE,
 & 600V ALTERNATOR
 4.3/5.0/5.7 LITER GM 2009 EMISSIONS

REV	DATE	ON COMPOSITE DWGS. SEE PART NO. FOR REVISION LEVEL	BY
-	2-27-09	NEW DRAWING [86172-7]	KRH

UNLESS OTHERWISE SPECIFIED -
 1) DIMENSIONS ARE IN MILLIMETERS
 2) TOLERANCES ARE:
 X.XX ± 0.25
 X.X ± 1.0
 X ± 1.5
 ANGLES ± 0° 30' MAX.
 SURFACE FINISH
 THIRD ANGLE PROJECTION

APPROVALS	DATE
DRAWN KRH	2-27-09
CHECKED CWF	2-27-09
APPROVED JAS	2-27-09

KOHLER CO. METRIC PRO-E
 POWER SYSTEMS, KOHLER, WI 53044 U.S.A.
 THIS DRAWING IN DESIGN AND DETAIL IS KOHLER CO.
 PROPERTY AND MUST NOT BE USED EXCEPT IN
 CONNECTION WITH KOHLER CO. WORK. ALL RIGHTS OF
 DESIGN OR INVENTION ARE RESERVED.

TITLE: **DIMENSION PRINT**
40/45 GM ACCESSORIES
 SCALE: 0.15 CAD NO. SHEET 1 of 1
 DWG NO.: **ADV-7689**